


KHA SLIM 220 LED C/EW

Part number 06081396



Description

Luminaire for indoor and outdoor floor mount, comprising:

- Electropolished AISI 316 stainless steel or aluminium body and top-cap polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5) depending on versions
- Clear UV-stabilised and impact-resistant technopolymer diffuser
- Extra pure polished aluminium reflector
- Anti-ageing custom moulded silicone sealing gasket(s)
- Electrical connection with quick disconnect connector in PA66 without halogens and phosphorus with silver-plated copper contacts, for cables Ø 9 - Ø 14 mm
- LED versions are manufactured with high performance LED arrays
- Anodised extruded aluminium profile for correct dissipation of the LED light source
- Stainless steel locking hardware
- Technopolymer electrical gearbox
- Concrete installation fixing rods are available as accessories (ordered separately)
- Die-cast aluminium floor mount base polyester powder coat finish prior chemical surface conversion
- KHA SLIM 220 floor installation can be done through a galvanised steel plinth to be directly buried in concrete or with a stainless steel base to be fastened to the floor with anchor bolts (included)
- Design by SILVIA PAOLA PENNACCHIO
- Design by SILVIA PAOLA PENNACCHIO

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

Product data

ETIM Group:	EG000027	ETIM Class:	EC000301
-------------	----------	-------------	----------

General information

Lampholder:	LED	Light source:	LED
Lightsource lumen output [lm]:	1733	Luminaire lumen output [lm]:	546
Luminaire wattage [W]:	13 W	Luminous efficacy [lm/W]:	42
CRI:	80	Colour temperature [K]:	4000
Colour / Finishing:	AN-g6 / Anthracite gray / Textured	IP degree of protection:	IP66
Impact resistance / impact energy:	IK09 10J xx7	Protection class:	II
Optic:	C/EW - Circular Extra-Wide	Net weight [kg]:	4.725
Overall diameter [mm]:	90	Overall height [mm]:	2200

Mechanical features

Shape:	Round \leq 150 mm	Housing material:	Aluminium
Diffuser material:	Plastic	Glow wire test [°C]:	650 °C

Electrical features

Voltage type:	AC/DC	Input voltage [V AC]:	220/240
Input frequency [Hz]:	0/50/60	Power factor / COS Φ :	0.9
Input voltage [V DC]:	176/280	Surge protection Common [kV]:	4.000000
Inrush current [A/ μ s]:	65 / 170	C10 1.5 mm ² :	5
C16 2.5 mm ² :	9	B10 1.5 mm ² :	3
B16 2.5 mm ² :	5		

Installation


Application area:	Outdoor lighting	Mounting type:	Bollard and column
Min. ambient temperature [°C]:	-20	Max. ambient temperature [°C]:	30

Light features

MacAdam:	3	Lumen maintenance:	L80B10@50000h
Distribution of light emission:	Direct	Luminous Intensity Class:	G*2
Zero light pollution (ULR = 0%):			


To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/gr/company/led-warranty>

Photometric data



Optional accessories

KHA SLIM



14071220

Hot dipped galvanised fixing base for recessing into concrete (suitable only for models 220/250 cm height)

■ INOX / Stainless steel



14071120

AISI 316 stainless steel floor installation base (suitable only for models 220/250 cm height)