


LANTERNA NK 21

Part number 3102572



Description

Indoor and outdoor wall-mount luminaire, comprising:

- Die-cast aluminium housing and trim, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Pressed glass diffuser, internally coated, secured with the ring
- Aluminium reflector and gear tray
- Technopolymer silicone sealing gasket
- Burnished stainless steel fixing screws
- Built-in driver
- Design by ROBERTO FIORATO
- Design by ROBERTO FIORATO

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

Product data

| | | | |
|-------------|----------|-------------|----------|
| ETIM Group: | EG000027 | ETIM Class: | EC001745 |
|-------------|----------|-------------|----------|

General information

| | | | |
|------------------------------------|-----------------------------|------------------------------|-------|
| Lampholder: | LED | Light source: | LED |
| Lightsource lumen output [lm]: | 1282 | Luminaire lumen output [lm]: | 755 |
| Luminaire wattage [W]: | 11 W | Luminous efficacy [lm/W]: | 69 |
| CRI: | 80 | Colour temperature [K]: | 4000 |
| Colour / Finishing: | RB-10 / Rust / Textured | IP degree of protection: | IP65 |
| Impact resistance / impact energy: | IK06 1J xx3 | Protection class: | I |
| Optic: | S/EW - Symmetric Extra-Wide | Net weight [kg]: | 1.826 |
| Overall length [mm]: | 167 | Overall width [mm]: | 133 |
| Overall height [mm]: | 216 | | |

Mechanical features

| | | | |
|--------------------|-------------|-------------------|-----------|
| Shape: | Rectangular | Housing material: | Aluminium |
| Diffuser material: | Glass | | |

Electrical features

| | | | |
|------------------------------|--------|-----------------------------|---------|
| Voltage type: | AC | Input voltage [V AC]: | 220/240 |
| Input frequency [Hz]: | 50/60 | Power factor / COS Φ : | 0.9 |
| Inrush current [A/ μ s]: | 5 / 30 | C10 1.5 mm ² : | 57 |
| C16 2.5 mm ² : | 92 | B10 1.5 mm ² : | 57 |
| B16 2.5 mm ² : | 92 | | |


Installation

| | | | |
|--------------------------------|------------------|--------------------------------|----------|
| Application area: | Outdoor lighting | Mounting type: | Bulkhead |
| Min. ambient temperature [°C]: | -20 | Max. ambient temperature [°C]: | 30 |

Light features

| | | | |
|---------------------------------|--------|--------------------|----------------|
| MacAdam: | 3 | Lumen maintenance: | L80B10@100000h |
| Distribution of light emission: | Direct | | |

Photometric data



To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>