

SL720SL L LED MICROPRISMA

Part number 8720761118410



Description

Free-standing (SL) LED luminaire for indoor, comprising:

- Steel sheet head, extruded aluminium profile post, steel sheet base, polyester powder coat finish
- Angle of the lamp head adjustable using a set screw
- Practical U-shaped base enables luminaire to be positioned flexibly and flush to a writing desk
- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
- Direct / indirect light distribution
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Complete with flexible power cord with plug
- VDU application suitable acc. to EN 12464-1
- Sensor device available with task oriented PIR detector and daylight control
- 3000K (CCT) versions available. Consult factory
- Special colour versions available. Consult factory
- For the innovative lighting technology of these lights patent is applied for (No. 10201511701.2)

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

Product data

ETIM Group:	EG000027	ETIM Class:	EC000300
-------------	----------	-------------	----------

General information

Lampholder:	LED	Light source:	LED
Lightsource lumen output [lm]:	16000	Luminaire lumen output [lm]:	14040
Luminaire wattage [W]:	110 W	Luminous efficacy [lm/W]:	128
CRI:	80	Colour temperature [K]:	4000
Colour / Finishing:	WH-RAL9016 / White RAL9016 / Textured	IP degree of protection:	IP20
Impact resistance / impact energy:	IK05 0.7J xx3	Protection class:	I
Optic:	S/D - Symmetric mainly indirect	Beam angle:	2 x 46° / 45°
Net weight [kg]:	16.733	Overall length [mm]:	430
Overall width [mm]:	705	Overall height [mm]:	2042

Mechanical features

Shape:	Rectangular	Housing material:	Aluminium
Diffuser material:	Plastic	Glow wire test [°C]:	650 °C

Electrical features

Voltage type:	AC	Input voltage [V AC]:	220/240
Input frequency [Hz]:	220-240V 50/60Hz	Power factor / COS Φ:	0.9
Input voltage [V DC]:	168/275	Inrush current [A/μs]:	26 / 140
C10 1.5 mm ² :	37	C16 2.5 mm ² :	61
B10 1.5 mm ² :	22	B16 2.5 mm ² :	36
EEL:	A1		

Installation


Application area:	Indoor lighting	Mounting type:	Free standing
Min. ambient temperature [°C]:	10	Max. ambient temperature [°C]:	40

Light features

MacAdam:	3	Lumen maintenance:	L80B10@50000h
Distribution of light emission:	Direct/Indirect	DFF - Downward Flux Fraction [%]:	12
UFF - Upward Flux Fraction [%]:	88		


To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

Photometric data




Optional accessories

SL720SL LED



8118000257

Remote control "Master" for versions with a sensor function



8118000647

Remote control "User" for versions with a sensor function

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>