


MERCURY PL M2 BLACK TR

Part number 8807211323382



Description

Suspended, LED luminaire for indoor, comprising:

- Luminaire head made from glass with moulded designer cover in a wave shape and moulded technopolymer moulded canopy
- Pendant tube made from metal and cable suspension on one side
- High transparent glass with a black ceramic edge (BLACK TR) and integrated micro prism diffuser for efficient light distribution, glare minimisation, and excellent uniformity
- Direct light distribution
- LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
- Colour tolerance according to MacAdam ≤ 3 SDCM
- VDU application suitable acc. to EN 12464-1
- Special colour versions available. Consult factory
- Pendant tube, cable suspension, supply cable and ceiling canopy included
- Design by WALTER DE SILVA
- Design by WALTER DE SILVA

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

Product data

| | | | |
|-------------|----------|-------------|----------|
| ETIM Group: | EG000027 | ETIM Class: | EC001743 |
|-------------|----------|-------------|----------|

General information

| | | | |
|------------------------------------|-------------------------------------|------------------------------|---------------|
| Lampholder: | LED | Light source: | LED |
| Lightsource lumen output [lm]: | 6110 | Luminaire lumen output [lm]: | 3600 |
| Luminaire wattage [W]: | 34 W | Luminous efficacy [lm/W]: | 106 |
| CRI: | 80 | Colour temperature [K]: | 3000 |
| Colour / Finishing: | BK-RAL9005 / Black RAL9005 / Glossy | IP degree of protection: | IP20 |
| Impact resistance / impact energy: | IK04 0.5J xx3 | Protection class: | I |
| Optic: | S/A - Symmetric direct | Beam angle: | 2 x 46° / 45° |
| Net weight [kg]: | 14 | Overall length [mm]: | 1753 |
| Overall width [mm]: | 347 | Overall height [mm]: | 1000 |

Mechanical features

| | | | |
|--------------------|-------------|----------------------|---------|
| Shape: | Rectangular | Housing material: | Plastic |
| Diffuser material: | Glass | Glow wire test [°C]: | 650 °C |

Electrical features

| | | | |
|---------------------------|------------------|---------------------------|----------|
| Voltage type: | AC | Input voltage [V AC]: | 220/240 |
| Input frequency [Hz]: | 220-240V 50/60Hz | Power factor / COS Φ: | 0.9 |
| Input voltage [V DC]: | 176/276 | Inrush current [A/μs]: | 25 / 200 |
| B10 1.5 mm ² : | 21 | B16 2.5 mm ² : | 34 |
| EEL: | A2 | | |

Installation


| | | | |
|--------------------------------|-----------------|--------------------------------|-----------|
| Application area: | Indoor lighting | Mounting type: | Suspended |
| Min. ambient temperature [°C]: | 10 | Max. ambient temperature [°C]: | 40 |

Light features

| | | | |
|---------------------------------|--------|-----------------------------------|---------------|
| MacAdam: | 3 | Lumen maintenance: | L80B10@50000h |
| Distribution of light emission: | Direct | DFF - Downward Flux Fraction [%]: | 100 |
| UFF - Upward Flux Fraction [%]: | 0 | UGR max.: | 19.0 |

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

Photometric data



To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>