



Open



Grill



V Shade

Surface-mount doorway and hallway lights and post mount series. Fixtures consist of:



- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free die-cast aluminum housing, ring, and faceplates.
- High transmittance, internally coated, soda-lime pressed glass diffuser, thermally and chemically quenched to strengthen the impact resistance and reduce the effect of rapid temperature changes.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- High-efficiency COB, combined with an optimized passive cooling system, provides a long LED life.

- 100% uniform diffused light emission.
- Input voltage: 120-277 V (50 / 60 Hz), integral driver.
- Consult factory for dimming options, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options including static colors.
- Wall bracket and post accessories available (ordered separately).
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty on components.
- 10-year warranty on glass.
- Marine Grade finish.
- Suitable for Natatorium applications.



FINISHES

- AN-96 / Iron gray / Textured
- RB-10 / Iron rust / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- BK-81 / Black / Textured



NIKKO  
+21 LED

Lumen Output	27K	3K	35K	4K	5K
Nikko+21	784	803	821	840	858
Nikko+21 Grill	429	439	449	459	469
Nikko+21 Visa	367	381	395	409	423

11 W Max Wattage

Scan here  
for installation  
instructions



# Order Guide - Nikko+21




Order code example


N21-V-11-IG-3K-120-NA-WB

80 CRI STANDARD - OTHER OPTIONS AVAILABLE


N21-

Trim Style	Wattage	Finish	Kelvin	Voltage	Controls	Accessories
<b>OP</b> Open  <b>G</b> Grill  <b>V</b> Shade	<b>11</b> 11 watt (max)  <b>XX</b> Specify Wattage Must be below max	<b>AM</b> Aluminum Metallic  <b>IG</b> Iron Gray  <b>IR</b> Iron Rust  <b>BK</b> Textured Black  <b>WH</b> Textured White  <b>CC</b> Custom Color	<b>27K</b> 2700k  <b>3K</b> 3000k  <b>35K</b> 3500k  <b>4K</b> 4000k  <b>5K</b> 5000k  <b>65K</b> 6500k  <b>RED</b> Static Red  <b>BLU</b> Static Blue  <b>GRN</b> Static Green  <b>RGBW*</b> RGBW  *See below for details	<b>UNV</b> 120-277V	<b>NA</b> Non Dimming  <b>0-10V</b> 0-10V Dimming Driver  <b>ELV</b> 120V Line-Voltage Dimming Driver	<b>REM</b> Remote Mounted Emergency Battery Back Up  <b>WB</b> Wall Bracket Not Required for standard wall mounting  <b>P7</b> 7.8" Post  <b>P22</b> 22.95" Post  <b>P32</b> 32.79" Post  <b>BABAA</b> Build America Buy America Act compliant   <p><b>COMPLETE UNIT</b>            1A+1B = 2 codes            2A+1B = 3 codes            COMPONENTS  <b>A</b> luminaire  <b>B</b> post</p>


WALL BRACKET AND POSTS ARE SUITABLE FOR ONE OR TWO FIXTURES EACH




WB  
Wall Bracket



P7  
7.8" Post



P22  
22.95" Post



P32  
32.79" Post

Performance in Lighting reserves the right to make all necessary changes without prior notice.

Performance in Lighting - 2621 Keys Pointe - Conyers, Georgia 30013 - USA - voice 770.822.2115 - info.usa@pil.lighting  
www.performanceinlighting.com

Revision 10  
04/25

## REMOTE RGBW ACCESSORIES

### Power Supply



**17433**  
Kit driver 48V



**17096**  
Kit driver 48V WP

### RF Controls



**3104173**  
RGBW RF controller 4 channel  
(0.35A each CH)



**31041730**  
RGBW RF controller WP 4 channel  
(0.35A each CH)



**310429**  
RGBW hand held remote

### DMX Controls



**178973**  
RGBW DMX enabler/decoder 4  
channel (0.35A each CH)



**1789730**  
RGBW DMX enabler/decoder WP 4  
channel (0.35A each CH)



**11015**  
Terminating Resistor



**110150**  
Terminating Resistor WP