

STEEL SQUARE 20



In-ground series. Fixtures consist of:


- Copper-free die-cast aluminum housing and die-cast corrosion-resistant AISI 316 stainless steel trim.
- Extra-clear, flat, tempered silk-screened soda-lime glass diffuser.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- Custom MCPCB utilized to maximize heat dissipation and promote a long LED life.
- High-transmittance transparent optics.
- Standard aimable optic system ($\pm 7^\circ$).
- $8^\circ \times 8^\circ$ beam angle (C/I).
- $10^\circ \times 45^\circ$ beam angle (ELL).
- Input voltage: 120-277 V (50 / 60 Hz), integral driver.
- Pre-wired cable connects luminaire with WATER-STOP connection system, suitable for through wiring. Included cable glands accept cables from $\text{Ø}0.35''$ up to $\text{Ø}0.63''$.

- Each rough-in kit is provided with a protective faceplate to avoid possible deformations during the installation in concrete to simplify installation.
- Consult factory for dimming options, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options.
- Consult factory for frosted or non-slip glass options.
- Thermoplastic compression-molded rough-in kit to be ordered separately.
- For outdoor inground applications, provide drainage gravel at least 12" below the rough-in or a suitable drainage system.
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty.



FINISHES

- INOX / Stainless steel / Matt
- BK-81 / Black / Textured
- AN-96 / Iron gray / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- RB-10 / Iron rust / Textured



STEEL SQUARE
20

Light Emission	Wattage	Optics	Finish	Kelvin	Voltage	Controls	Accessories
3 3LED	4.2 4.2 watt (3LED Max)	8 8° Beam	AM Aluminum Metallic	27K 2700k	120 120 volts	NA Non Dimming	NS Non-Slip Glass
6 6LED	7.6 7.6 watt (6LED Max)	ELL 10°x45° Beam FRST Diffuse light	IG Iron Gray IR Iron Rust BK Textured Black WH Textured White CC Custom Color	3K 3000k 35K 3500k 4K 4000k 6K 6000K	277 277 volts	0-10V 0-10V Dimming ELV ELV Dimming	HEX Hexcell Louver