

# STEEL SQUARE 28



In-ground series. Fixtures consist of:


- Copper-free die-cast aluminum housing and die-cast corrosion-resistant AISI 316 stainless steel trim.
- Extra-clear, flat, tempered silk-screened soda-lime glass diffuser.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- Custom MCPCB utilized to maximize heat dissipation and promote a long LED life.
- Standard aimable optic system ( $\pm 7^\circ$ ).
- High-transmittance transparent optics.
- $8^\circ \times 8^\circ$  beam angle (C/I).
- $10^\circ \times 45^\circ$  beam angle (ELL).
- Input voltage: 120-277 V (50 / 60 Hz), integral driver.
- Pre-wired cable connects luminaire with WATER-STOP connection system, suitable for through wiring. Included cable glands accept cables from  $\varnothing 0.35"$  up to  $\varnothing 0.63"$ .

- Each rough-in kit is provided with a protective faceplate to avoid possible deformations during the installation in concrete to simplify installation.
- Consult factory for dimming options, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options.
- Consult factory for frosted or non-slip glass options.
- Thermoplastic compression-molded rough-in kit to be ordered separately.
- For outdoor inground applications, provide drainage gravel at least 12" below the rough-in or a suitable drainage system.
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty.



## FINISHES

- INOX / Stainless steel / Matt
- BK-81 / Black / Textured
- AN-96 / Iron gray / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- RB-10 / Iron rust / Textured



STEEL SQUARE  
28

Light Emission	Wattage	Finish	Kelvin	Voltage	Controls	Accessories
		<b>SS</b> Stainless Steel		<b>120</b> 120 volts	<b>NA</b> Non Dimming	
		<b>AM</b> Aluminum Metallic		<b>277</b> 277 volts	<b>0-10V</b> 0-10V Dimming	
	77.6 watt(6LE)	<b>IG</b> Iron Gray			<b>ELV</b> ELV Dimming	
		<b>IR</b> Iron Rust				
		<b>BK</b> Textured Black				
		<b>WH</b> Textured White				
		<b>CC</b> Custom Color				