

# Q-CEILING



Ceiling mount series. Fixtures consist of:


- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free extruded aluminum housing and copper-free precision die-cast aluminum ring/faceplate, bracket and mounting plate.
- Extra-clear, tempered, silk-screened, flat glass diffuser.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- High-efficiency COB, combined with an optimized passive cooling system, provides a long LED life.
- Internal specular reflector coated with 5-layers of PVD 99.98% pure aluminum providing >95% reflection.
- Circular Intensive beam angle (C/I).
- Marine Grade finish .
- Suitable for Natatorium applications.

- Circular Medium beam angle (C/M).
- Diffuse light emission (SOFT).
- Input voltage: 120-277 V (50 / 60 Hz), integral 0-10 V dimming driver.
- Five optional finishes available. Add finish suffix to any part number for textured Black (BK-81), Iron gray (AN-96), Aluminum metallic (GR-94), White (WH-87), Iron rust (RB-10) when not standard.
- Consult factory for dimming options, marine-grade, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options including static colors.
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty.
- DarkSky approved in 3000K or below.



## FINISHES

- AN-96 / Iron gray / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- BK-81 / Black / Textured
- RB-10 / Iron rust / Textured



Q  
CEILING

Lumen Output 30W	27K	3K	35K	4K	5K
Q-Ceiling 20°	2784	2876	2968	3061	3153
Q-Ceiling 40°	2769	2861	2953	3045	3137
Q-Ceiling 85°	2804	2897	2990	3084	3177
Q-Ceiling Soft	2190	2270	2350	2430	2510

Scan here  
for installation  
instructions



# Order Guide - Q-CEILING




Order code example

QCE-30W-C/I-IG-3K-UNV-ELV

Series	Wattage	Optics	Finish	Kelvin	Voltage	Controls	Accessories
QCE Q-Ceiling	<b>16W</b> 16 watt (AMB Max)	<b>C/I</b> 20° Beam	<b>AM</b> Aluminum Metallic	<b>27K</b> 2700K	<b>UNV</b> 120-277V	<b>0-10V</b> 0-10V Dimming Driver (standard)	<b>CON2</b> (double-gang j-box, adaptor plate and 1/2" knockouts)
	<b>18W</b> 18 watt	<b>C/M</b> 40° Beam	<b>IG</b> Iron Gray	<b>3K</b> 3000K			
	<b>20W</b> 20 watt	<b>C/EW</b> 85° Beam	<b>IR</b> Iron Rust	<b>35K</b> 3500K		<b>ELV</b> 120V Line- Voltage Dimming Driver	<b>CON4</b> (double-gangj-box, adaptor plate and 3/4" knockouts)
	<b>30W</b> 30 watt (max)	<b>SOFT</b> Diffused Light	<b>BK</b> Textured Black	<b>4K</b> 4000K			
	<b>XX</b> Specify wattage must be under max		<b>WH</b> Textured White	<b>5K</b> 5000K			
			<b>CC</b> Custom Color	<b>RED</b> Red		Consult factory for more options	<b>REM</b> Remote mounted Emergency battery back-up
				<b>BLU</b> Blue			
				<b>GRN</b> Green			
				<b>AMB</b> Amber (16W max)			
				<b>RGBW*</b> RGBW			
				*See below for control details			

80 CRI STANDARD - OTHER OPTIONS AVAILABLE



CON

Surface Mounted  
J-box with Conduit Entry

Performance in Lighting reserves the right to make all necessary changes without prior notice.

Performance in Lighting - 2621 Keys Pointe - Conyers, Georgia 30013 - USA - voice 770.822.2115 - info.usa@pil.lighting  
www.performanceinlighting.com

Revision 14  
04/25

## RGBW ACCESSORIES

### Power Supply



17433  
Kit driver 48V



17096  
Kit driver 48V WP

### RF Controls



3104173  
RGBW RF controller 4 channel  
(0.35A each CH)



31041730  
RGBW RF controller WP 4 channel  
(0.35A each CH)



310429  
RGBW hand held remote

### DMX Controls



178973  
RGBW DMX enabler/decoder 4  
channel (0.35A each CH)



1789730  
RGBW DMX enabler/decoder WP 4  
channel (0.35A each CH)