

# SPILLO



Area and site lighting series. Fixtures consist of:


- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free precision die-cast aluminum housing and top cap.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- Custom MCPCB utilized to maximize heat dissipation and promote a long LED life.
- High-transmittance transparent optics.
- The "Secure Light Distribution" system can bypass individual diodes in the event of a single LED failure to ensure continuous uniform light distribution.
- IESNA Type II light distribution.
- IESNA Type V light distribution.
- Input voltage: 120-277 V (50 / 60 Hz), integral 0-10 V dimming driver.

- Integral surge protector can withstand up to 10 kV transient line surge.
- Pre-wired factory sealed cable for external electrical connection included.
- Consult factory for dimming options, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options.
- Consult factory for custom pre-wired factory sealed cable length options.
- Consult factory for pole information.
- Consult factory for wall bracket accessory, multi-head pole top mounting, and other custom options.
- Ø3" and Ø4" post top adapters, and poles in 8' / 10' / 12' / 14' options available (ordered separately).
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty.
- Marine Grade finish.
- Suitable for Natatorium applications.



## FINISHES

- AN-96 / Iron gray / Textured
- BK-81 / Black / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- RB-10 / Iron rust / Textured



SPILLO

Lumen Output	3K	4K
Spillo T5	4052	4357
Spillo T2	4177	4492

# Order Guide - Spillo



Order code example

**SPILLO-T2-65-AM-3K-120-NA-4"/P8**

SPILLO-

--	--	--	--	--	--

Light Output	Wattage	Finish	Kelvin	Voltage	Controls	Accessories
<b>T2</b> Type II	<b>65</b> 65 watt (max)	<b>AM</b> Aluminum Metallic	<b>27K</b> 2700K	<b>120</b> 120 volts	<b>NA</b> Non Dimming	<b>4"</b> 4" Pole top adapter
<b>T5</b> Type V	<b>XX</b> Specify Wattage Must be below max	<b>IG</b> Iron Gray	<b>3K</b> 3000k	<b>277</b> 277 volts	<b>0-10V</b> 0-10V Dimming	<b>3"</b> 3" Pole top adapter
		<b>IR</b> Iron Rust	<b>35K</b> 3500K		<b>ELV</b> ELV Dimming	<b>P8</b> 8' Pole (4")
		<b>BK</b> Textured Black	<b>4K</b> 4000k			<b>P10</b> 10' Pole (4")
		<b>WH</b> Textured White				<b>P12</b> 12' Pole (4")
		<b>CC</b> Custom Color				<b>P14</b> 14' Pole (4")
						<b>P16</b> 16' Pole (4")
						<b>P18</b> 18' Pole (4")
						<b>PXX</b> Specify Pole height
						Consult factory for more options

**SPILLO**




90013  
Adapter pole top 3"




90014  
Adapter pole top 4"


**POLES**




71408  
Pole 8' (4" diameter)




71410  
Pole 10' (4" diameter)




71412  
Pole 12' (4" diameter)



71414  
Pole 14' (4" diameter)



71416  
Pole 16' (4" diameter)



71418  
Pole 18' (4" diameter)

**POLE DETAILS:**

Pole - The pole shaft is extruded from seamless alloy aluminum.

Handhole - A covered handhole with hardware and grounding provision are provided.

Anchor Base - The anchor base is cast from 356 alloy aluminum. The completed assembly is heat-treated to a T6 temper. Aluminum nut covers are included with anchor base unless otherwise specified.

Anchor Bolts - Anchor bolts conform to ASTM F1554 Grade 55 and are provided with two hex nuts and two flat washers. Bolts have an "L" bend on one end and are galvanized a minimum of 12" on the threaded end.

Finish - Powder coated to match the fixture unless specified different.

Consult factory for additional details or other pole options.

