

ALU SQUARE 1



Wall sconce series. Fixtures consist of:

- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free precision machined anodized aluminum housing and optical compartment.
- Clear UV-stabilized diffuser.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- Wall effects light emission.
- 6° x 6° beam angle (C/I).
- 25° x 25° beam angle (C/M).
- 40° x 40° beam angle (C/M).
- 10° x 45° beam angle (ELL).
- Input voltage is 120-277 V (50/60 Hz), integral driver for "120-277" models only.

- Matching junction box plate optional accessory available (ordered separately).
- For models not in the "120-277" category, a 700 mA constant current driver is available as an accessory or by others (to be removed). Consult factory for more information.
- Consult factory for dimming options, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options.
- Consult factory for custom optics options.
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty.
- Marine Grade finish.
- Suitable for Natatorium applications.




FINISHES

- BK-40 / Anodized black / Matt
- GR-EV1 / Anodized aluminum / Matt

WITH MOQ 30

- AN-96 / Iron gray / Textured
- BK-81 / Black / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- RB-10 / Iron rust / Textured



Lumen Output	27K	3K	35K	4K	6K
Alu 1 - 10°x45°	61	67	75	82	98
Alu 1 - 25°	63	68	74	79	91
Alu 1 - 40°	69	76	86	93	111
Alu 1 - 6°	80	85	92	98	111
Alu 1 - 120-277V-10°x45°	40	44	47	50	56
Alu 1 - 120-277V-25°	36	39	42	44	50
Alu 1 - 120-277V-40°	50	53	57	60	68
Alu 1 - 120-277V-6°	52	57	62	67	74

Order Guide - Alu Square 1



Order code example

AS1-RDR-AA-6-3K-120-NA

AS1-

--	--	--	--	--	--	--

Housing Style	Finish	Optics	Color Temperature	Voltage	Controls	Accessories
RDR Remote driver	AA Anodized Aluminum	6 6 degrees	27K 2700k	120 120 volts	NA Non Dimming	JBOX Jbox cover
IDR Integral driver	AB Anodized Black	25 25 degrees	3K 3000k	277 277 volts	0-10V 0-10V Dimming	RDR Remote Driver (1:1) Other options available
	40 40 degrees	35K 3500k	4K 4000k		ELV ELV Dimming	
	Finishes Below Available MOQ30 pieces	ELL 10x45 degrees	6K 6000k			
	AM Aluminum Metallic	WB Wide Beam	RED Static Red			
	IG Iron Gray		GRN Static Green			
	WH Textured White		BLU Static Blue			
	IR Iron Rust		AMB Amber			
	BK Textured Black					
	CC Custom Color					