

INSERT+2



Recessed wall step light series. Fixtures consist of:


- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free precision die-cast aluminum housing and ring/faceplate.
- Frosted, flat, tempered silk-screened soda-lime glass diffuser.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- Custom MCPCB utilized to maximize heat dissipation and promote a long LED life.
- IESNA Type III light distribution.
- Input voltage: 120-277 V (50 / 60 Hz), integral driver.

- Pre-wired factory sealed cable for external electrical connection included.
- Consult factory for dimming options, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options.
- Consult factory for custom pre-wired factory sealed cable length options.
- Stainless steel recessed rough-in kit to be ordered separately.
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty.
- Marine Grade finish.
- Suitable for Natatorium applications.



FINISHES

- AN-96 / Iron gray / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- BK-81 / Black / Textured
- RB-10 / Iron rust / Textured



INSERT+
2

Lumen Output	27K	3K	35K	4K	5K	6K
Insert+2	481	503	528	553	578	603

11W Max Wattage

Order Guide - Insert+2




Order code example


Wattage	Finish	Kelvin	Voltage	Controls	Accessories
8 8 watt	AM Aluminum Metallic	27K 2700k	120 120 volts	NA Non Dimming	SWR Shallow Wall Rough in
11 11 watt (max)	IG Iron Gray	3K 3000k	277 277 volts	ELV ELV Dimming	ADP Retrofit adaptor plate
XX Specify Wattage Must be below max	IR Iron Rust	35K 3500k			
	BK Textured Black	4K 4000k			
	WH Textured White	5K 5000k			
	CC Custom Color	AMB Static Amber Turtle Friendly (590nm)			
		RED Static Red			
		BLU Static Blue			
		GRN Static Green			
		RGBW RGBW Consult factory for control details			

ACCESSORIES

INSERT+




Standard Rough-In
Included with Fixture
310486
ROUGH-IN



Retrofit Adapter
Plate
ADP
Goof Ring

Contact Factory for
Custom Adapter Plates/
Goof Rings



Shallow Wall Rough-In
SWR Accessory
310486-BSL
ROUGH-IN

One 1/2" KO (Ø.875") on both sides.
(overall 10.5" tall x 11" wide x 2.5" deep)


OPTIONAL ACCESSORIES

DESCRIPTION	FINISH	PART NUMBER
Controls		
Kit driver 48V		17433
Kit driver 48V WP		17096
RF Controls		
RGBW RF controller 4 channel (0.4A each CH)		3104174
RGBW RF controller WP 4 channel (0.4A each CH)		31041740
RGBW hand held remote		310429
TW RF controller 4 channel (0.525A each CH)		3104275
TW RF controller WP 4 channel (0.525A each CH)		31042750
TW hand held remote		310421
WiFi Controls		
RGBW WiFi controller 4 channel (0.4A each CH)		3104164
RGBW WiFi controller WP 4 channel (0.4A each CH)		31041640
TW WiFi controller 4 channel (0.525A each CH)		3104265
TW WiFi controller WP 4 channel (0.525A each CH)		31042650
DMX Controls		
RGBW DMX enabler/decoder 4 channel (0.4A each CH)		178974
RGBW DMX enabler/decoder WP 4 channel (0.4A each CH)		1789740
TW DMX enabler/decoder 4 channel (0.525A each CH)		178975
TW DMX enabler/decoder WP 4 channel (0.525A each CH)		1789750
Terminating resistor		11015
Terminating resistor WP		110150



App (free) – “EasyLighting”

EasyLighting is an application that uses a WiFi network to control, adjust, and customize the lighting color or CCT, brightness, and the rate of change. With this application you can control EasyLighting products through most mobile devices



17433



17096



**3104174
3104275**



**31041740
31042750
31041640
31042650
1789740
1789750**



310429



310421



**3104164
3104265**



**178974
178975**



11015



110150