

INSERT+2



Recessed wall step light series. Fixtures consist of:


- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free precision die-cast aluminum housing and ring/faceplate.
- Frosted, flat, tempered silk-screened soda-lime glass diffuser.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- Custom MCPCB utilized to maximize heat dissipation and promote a long LED life.
- IESNA Type III light distribution.
- Input voltage: 120-277 V (50 / 60 Hz), integral driver.

- Pre-wired factory sealed cable for external electrical connection included.
- Consult factory for dimming options, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options.
- Consult factory for custom pre-wired factory sealed cable length options.
- Stainless steel recessed rough-in kit to be ordered separately.
- 5-year warranty.
- Marine Grade finish.
- Suitable for Natatorium applications.
- Consult factory for any Buy American Act (BAA) or Build America Buy America Act (BABAA) requirements.



FINISHES

- AN-96 / Iron gray / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- BK-81 / Black / Textured
- RB-10 / Iron rust / Textured



Lumen Output	27K	3K	35K	4K	5K	6K
Insert+2	481	503	528	553	578	603

11W Max Wattage

INSERT+
2

Scan here
for installation
instructions



Order Guide - Insert+2



Order code example


IN+2

Wattage	Finish	Kelvin	Voltage	Controls	Accessories
3 3 watt (min)	AM Aluminum Metallic	27K 2700k	UNV 120-277V	NA Non Dimming	ADP Retrofit adaptor plate
8 8 watt	IG Iron Gray	3K 3000k			
11 11 watt (max)	IR Iron Rust	35K 3500k	ELV 120V Line-Voltage Dimming Driver	TP Tamper Proof hardware	BABAA Build America Buy America Act compliant (not available for all options)
XX Specify Wattage Must be within range (3-11W)	BK Textured Black	4K 4000k			
	WH Textured White	5K 5000k			
	CC Custom Color	AMB Static Amber Turtle Friendly (590nm)			
		RED Static Red			
		BLU Static Blue			
	GRN Static Green				
	RGBW* RGBW See below for control details				


80 CRI STANDARD - OTHER OPTIONS AVAILABLE

ACCESSORIES

INSERT+



Standard Rough-In
Included with Fixture
310486
ROUGH-IN



Retrofit Adapter
Plate
ADP
Goof Ring
Contact Factory for
Custom Adapter Plates/
Goof Rings

Power Supply



17433
Kit driver 48V



17096
Kit driver 48V WP

RF Controls



3104173
RGBW RF controller 4 channel
(0.35A each CH)



31041730
RGBW RF controller WP 4 channel
(0.35A each CH)



310429
RGBW hand held remote

DMX Controls



178973
RGBW DMX enabler/decoder 4
channel (0.35A each CH)



1789730
RGBW DMX enabler/decoder WP 4
channel (0.35A each CH)



11015
Terminating Resistor



110150
Terminating Resistor WP