

MAGICCLICK OVAL




- Ceiling and wall mount series. Fixtures consist of:
- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
 - Copper-free die-cast aluminum housing, ring, and faceplates.
 - High transmittance, internally coated, soda-lime pressed glass diffuser, thermally and chemically quenched to strengthen the impact resistance and reduce the effect of rapid temperature changes.
 - The ring/faceplate is integral with the diffuser.
 - Custom molded, anti-aging gasket(s).
 - Stainless steel external hardware.
 - Suitable for Natatorium applications.
 - Marine Grade finish.

- Custom MCPCB utilized to maximize heat dissipation and promote a long LED life.
- 100% uniform diffused light emission.
- Input voltage: 120-277 V (50 / 60 Hz), integral driver.
- Standard hinge-style housing allows for a simplified installation.
- Consult factory for dimming options, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options.
- 5-year warranty on components.
- 10-year warranty on glass.
- Consult factory for any Buy American Act (BAA) or Build America Buy America Act (BABAA) requirements.




FINISHES


- AN-96 / Iron gray / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- BK-81 / Black / Textured
- RB-10 / Iron rust / Textured



MAGICCLICK
OVAL



MAGICCLICK
OVAL SHADE H



MAGICCLICK
OVAL SHADE V



Scan Here for
Installation Instructions

Lumen Output	27K	3K	35K	4K	5K
Magclick Oval	575	608	641	675	708
Magclick Oval Shade H	316	334	352	370	388
Magclick Oval Shade V	358	377	395	414	451

11W Max Wattage

Revision 07
06/25

Order Guide - Magiclick Oval



Order code example

MCO-OPEN-11-AM-3K-120-NA

MCO-

--	--	--	--	--	--	--

Trim Style	Wattage	Finish	Kelvin	Voltage	Controls	Options		
OPEN Open Trim	11 11 watt (max)	AM Aluminum Metallic	27K 2700K	UNV 120-277V	NA Non Dimming	REM Remote mounted Emergency battery back-up		
SH Horizontal Shade	XX Specify wattage must be below max	IG Iron Gray	3K 3000k				0-10V 0-10V Dimming	
SV Vertical Shade		IR Iron Rust	35K 3500k				ELV ELV Dimming	TP Tamper proof hardware
		4K 4000k						
		BK Textured Black	5K 5000K					
		WH Textured White	RED Static Red					
		CC Custom Color	BLU Static Blue					
		GRN Static Green		BABAA Build America Buy America Act compliant (not available for all options)				

80 CRI STANDARD - OTHER OPTIONS AVAILABLE

Performance in Lighting reserves the right to make all necessary changes without prior notice.

Performance in Lighting - 2621 Keys Pointe - Conyers, Georgia 30013 - USA - voice 770.822.2115 - info.usa@pil.lighting
www.performanceinlighting.com

Revision 07
06/25