

GUELL ZERO



Economical low-profile landscape flood light series.

Fixtures consist of:


- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free precision die-cast aluminum housing, ring/faceplate, and adjustable mounting arm.
- Extra-clear, flat, tempered silk-screened soda-lime glass diffuser.
- Custom molded, anti-aging gasket(s).
- High-efficiency COB, combined with an optimized passive cooling system, provides a long LED life.

- NEMA 6H x 5V light distribution (S/W).
- Input voltage: 120-277 V (50 / 60 Hz), integral 1-10 V dimming driver.
- Pre-wired factory sealed cable for external electrical connection included.
- Standard robust ½" NPS knuckle mount with 180° adjustable swivel arm (SA versions) and rugged, locking teeth for a simplified installation.
- 5-year warranty.
- Marine Grade finish.
- Suitable for Natatorium applications.



FINISHES

- GR-94 / Aluminum metallic / Textured
- RB-10 / Iron rust / Textured
- BK-81 / Black / Textured
- AN-96 / Iron gray / Textured
- WH-87 / White / Textured



Lumen Output	3K	4K
Guell+Zero 13W	1249	1549
Guell+Zero 26W	2569	2769

GUELL
ZERO

Order Guide - Guell Zero



Order code example

GZERO-26-AM-3K-120

GZERO-

--	--	--	--	--	--

Wattage	Finish	Color Temperature	Voltage	Controls	Accessories
13 13 watt	AM Aluminum Metallic	27K 2700K	120 120 volts	NA Non Dimming	
26 26 watt (max)	IG Iron Gray	3K 3000k	277 277 volts	0-10V 0-10V Dimming	
XX Specify wattage must be below max	IR Iron Rust	35K 3500K			
	BK Textured Black	4K 4000k			
	WH Textured White	6K 6000K			
	AMB Amber				
	BLU Static Blue				
	RED Static Red				
	CC Custom Color	GRN Static Green			