

# CRICKET+ 10



In-ground series. Fixtures consist of:

- Copper-free die-cast corrosion-resistant aluminum housing and trim.
- Copper-free die-cast corrosion-resistant aluminum housing.
- AISI 316 stainless steel trim.
- Extra-clear, tempered, silk-screened, flat glass diffuser.
- Frosted, tempered, silk-screened, flat glass diffuser (C/EW versions).
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- Custom MCPCB utilized to maximize heat dissipation and promote long LED life.
- High-transmittance transparent optics.
- Circular Intensive beam angle (C/I).
- Circular Medium beam angle (C/M).
- Diffuse light emission (C/EW).
- Input voltage: 120-277 V (50 / 60 Hz), integral driver.
- Pre-wired factory sealed cable for external electrical connection included.

- Each rough-in kit is provided with a protective faceplate to avoid possible deformations during the installation in concrete to simplify installation.
- Thermoplastic compression-molded rough-in kit can be ordered separately.
- For outdoor inground applications, provide drainage gravel at least 12" below the rough-in or a suitable drainage system.
- Frosted (FRST) and Non-Slip (NS) glass option available - add suffix to any part number.
- Consult factory for additional optic options.
- Consult factory for dimming options, marine-grade, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options including static colors.
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty.
- Marine Grade finish.
- Suitable for Natatorium applications.




## FINISHES

- AN-96 / Iron gray / Textured
- INOX / Stainless steel / Matt
- BK-81 / Black / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- RB-10 / Iron rust / Textured

Lumen Output	27K	3K	35K	4K	5K
<b>Cricket+10 C/EW</b>	<b>127</b>	<b>132</b>	<b>137</b>	<b>142</b>	<b>147</b>
<b>Cricket+10 C/I</b>	<b>400</b>	<b>415</b>	<b>430</b>	<b>446</b>	<b>461</b>
<b>Cricket+10 C/M</b>	<b>391</b>	<b>406</b>	<b>421</b>	<b>436</b>	<b>451</b>

6W Max Wattage



CRICKET+  
10



Scan here  
for installation  
instructions

FIXTURES INCLUDE 120-277V 50/60HZ INTEGRAL DRIVERS UNLESS OTHERWISE NOTED

Revision 20  
02/25

# Order Guide - Cricket+



Order code example

**C+-10-6-C/I-AM-3K-NA-FRST**

**C+**


Housing Style	Wattage	Optics	Finish	Kelvin	Voltage	Controls	Options
<b>10</b> Cricket+10	<b>3.5</b> 3.5 watt RGBW/TW Remote Only  <b>6</b> 6 watt Cricket (Max)  <b>XX</b> Specify wattage must be below max  <b>Wattages below 6W must be Remote</b>	<b>C/I</b> 8°  <b>C/M</b> 30°  <b>C/EW</b> 88°	<b>AM</b> Aluminum Metallic  <b>IG</b> Iron Gray  <b>IR</b> Iron Rust  <b>BK</b> Textured Black  <b>WH</b> Textured White  <b>BRS</b> Brass  <b>SS</b> Stainless Steel  <b>CC</b> Custom Color	<b>27K</b> 2700K  <b>3K</b> 3000k  <b>35K</b> 3500K  <b>4K</b> 4000k  <b>AMB</b> Static Amber  <b>RED</b> Static Red  <b>BLUE</b> Static Blue  <b>RGBW*</b> (3.5W) 4K White C/M Only  <b>TW*</b> Tunable White (3.5W)  *See below for control details	<b>UNV</b> 120-277V  not suitable for RGBW or TW	<b>NA</b> Non Dimming  <b>0-10V</b> 0-10V Dimming Remote only +10	<b>RDR</b> Remote Driver  <b>FRST</b> Frosted Glass  <b>NS</b> Non-Slip Glass  <b>LVR</b> Hex Louver

## INCLUDED ACCESSORIES


DESCRIPTION	FINISH	PART NUMBER
<b>CRICKET+ 10</b>		
Recessed fixing kit		<b>3109879</b>
Recessed fixing kit - RGBW/TW		<b>3113571</b>

80 CRI STANDARD - OTHER OPTIONS AVAILABLE

### Rough-in Kit CRICKET+ 10 RGBW/TW




**3109879**



**3113571**

OPTIONAL RGBW ACCESSORIES

DESCRIPTION	FINISH	PART NUMBER
<b>Controls</b>		
Kit driver 48V		<b>17433</b>
Kit driver 48V Wet Location		<b>17096</b>



Product is supplied with integral DMX controllers, and remote 48VDC power supply. Controls by others.

TECHNICAL DATA

CRICKET+10

