# KHA CITY 24

Performance Lighting






Pathway bollard series. Fixtures consist of:

- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free (<1%) precision die-cast aluminum housing and top cap.
- Copper-free (<1%) aluminum extruded post.
- Corrosion-resistant AISI 316 stainless steel post and top cap.
- Clear UV-stabilized, high-impact resistant diffuser.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- Internal specular reflector coated with 5-layers of PVD 99.98% pure aluminum providing >95% reflection.
- Custom MCPCB utilized to maximize heat dissipation and promote long LED life.
- High-transparency polycarbonate optics for optimized light transmission.
- Type III light distribution.
- Type V light distribution.
- Marine Grade Finish.
- 5-year warranty.
- Input voltage: 120-277 V (50 / 60 Hz), integral driver.
- The luminaire may be configured with numerous options and multiple standard finishes. Not all options are available in all configurations. Consult factory for more information about specification sheet details to build your light.
- Steel ground base plate included for bollards.
- Concrete installation fixing rods available (ordered separately).
- Bolt-on root galvanized steel plinth or stainless steel flange plate (anchor plugs not included) floor mounting options available for all KHA CITY 24 options (ordered separately)
- Suitable for most coastal applications (stainless steel versions).
- DarkSky approved in 3000K or below.
- Rated for 100-mph wind load -custom poles available for higher wind loads upon request.


IP 66 · WET · FULL CUT OFF · cULus LISTED · DARKSKY APPROVED · 0-10 V · RAL

## FINISHES

- **AN-96** / Iron gray / Textured
- **BK-81** / Black / Textured
- **INOX** / Stainless steel / Matt
- **GR-94** / Aluminum metallic / Textured
- **WH-87** / White / Textured
- **RB-10** / Iron rust / Textured




KHA CITY 24




KHA CITY COMFORT 24

**Scan here for installation instructions**

Performance in Lighting reserves the rights to make all necessary changes without prior notice.

**Performance in Lighting** - 2621 Keys Pointe - Conyers, Georgia 30013 - USA - voice 770.822.2115 - info.usa@pil.lighting
**www.performanceinlighting.com**

Rev. 09/12/2026

# Order Guide - KHA CITY 24

Order code example **KHACT24-94-10W-3K-SS-UNV-010V-DB**

| Series | Bollard Height | Wattage | CCT | Distribution | Finish | Voltage | Dimming | Options/ Accessories |
|---|---|---|---|---|---|---|---|---|
| **KHACT24**<br>KHA City 24<br><br>**KHACT24C**<br>KHA City Comfort24<br><br>**KHACT24M**<br>KHA City Marine 24<br>*Stainless Steel only* | **94**<br>94 inch* (max)<br><br>**24**<br>24 inch (min)<br><br>**XX**<br>Specify bollard height must be within range | **10W**<br>10 watt<br><br>**15W**<br>15 watt<br><br>**20W**<br>20 watt*<br><br>**23W**<br>23 watt*<br><br>**XX**<br>Specify wattage must be within range<br><br>*Standard wattages<br>T3- 20W<br>T5- 23W | 80 CRI std.<br><br>**22K**<br>2200k<br><br>**27K**<br>2700k<br><br>**3K**<br>3000k*<br><br>**35K**<br>3500k<br><br>**4K**<br>4000k*<br><br>**5K**<br>5000k<br><br>**57K**<br>5700k<br><br>**65K**<br>6500k | **T3**<br>Type 3<br>20W max<br><br>**T5**<br>Type 5<br>23W max | **BK**<br>Textured Black*<br><br>**IG**<br>Iron Gray*<br><br>**AM**<br>Aluminum Metallic<br><br>**WH**<br>Textured White<br><br>**IR**<br>Iron Rust<br><br>**SS**<br>Stainless Steel<br>*Marine Only<br><br>**CC**<br>Custom Color* | **UNV**<br>120-277V*<br><br>**120V**<br>120V Only<br><br>**347V**<br>Integral Tranformer<br><br>**480V**<br>Integral Tranformer | **010V**<br>0-10V Dimming Driver*<br><br>**ELV**<br>120V Line-Dimming<br><br>Contact EMPK Battery up Options | **DB**<br>Direct burial base<br><br>**EMPK**<br>Intergral 15W EMPK<br><br>**RGFCI**<br>Recessed outlet with cover- GFCI/USB<br><br>Template & Anchor bolts included with fixture |

CONSULT FACTORY FOR OTHER AVAILABLE OPTIONS NOT SHOWN ABOVE

## REQUIRED FOR INSTALLATION **Included with Fixture**

| DESCRIPTION | FINISH | PART NUMBER |
|---|---|---|
| **KHA CITY** | | |
| Concrete mounting adaptor with stainless steel plate and galvanised steel rods | | **3115347** |
| BASE KHA CITY 24 USA | | **07968** |




**3115347**



**07968**

## OPTIONAL ACCESSORIES

| DESCRIPTION | FINISH | PART NUMBER |
|---|---|---|
| **KHA CITY** | | |
| DIRECT BURIAL BASE KHA CITY 24 USA | | **07969** |



**07969**

| KHA CITY 24 | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| **Wattage (Distribution)** | **2200K** | **2700K** | **3000K** | **3500K** | **4000K** | **5000K** | **5700K** | **6500K** |
| 10W COMFORT (Type III) | 613 | 701 | 729 | 741 | 761 | 761 | 745 | 743 |
| 10W (Type III) | 536 | 614 | 638 | 639 | 665 | 665 | 652 | 650 |
| 15W COMFORT (Type III) | 913 | 1044 | 1086 | 1104 | 1133 | 1133 | 1110 | 1106 |
| 15W (Type III) | 799 | 914 | 951 | 952 | 991 | 991 | 971 | 967 |
| 20W COMFORT (Type III) | 1239 | 1417 | 1474 | 1499 | 1538 | 1538 | 1506 | 1501 |
| 20W (Type III) | 1084 | 1240 | 1290 | 1292 | 1345 | 1345 | 1317 | 1313 |
| 10W COMFORT (Type V) | 715 | 818 | 851 | 859 | 895 | 895 | 876 | 874 |
| 10W (Type V) | 846 | 968 | 1007 | 1017 | 1060 | 1060 | 1038 | 1034 |
| 15W COMFORT (Type V) | 1063 | 1216 | 1265 | 1278 | 1330 | 1330 | 1303 | 1299 |
| 15W (Type V) | 1258 | 1439 | 1497 | 1512 | 1575 | 1575 | 1542 | 1537 |
| 23W COMFORT (Type V) | 1643 | 1879 | 1955 | 1974 | 2056 | 2056 | 2014 | 2007 |
| 23W (Type V) | 1944 | 2224 | 2313 | 2337 | 2434 | 2434 | 2384 | 2376 |

Performance in Lighting reserves the rights to make all necessary changes without prior notice.
**Performance in Lighting** - 2621 Keys Pointe - Conyers, Georgia 30013 - USA - voice 770.822.2115 - info.usa@pil.lighting
**www.performanceinlighting.com**