







Recessed wall steplight series. Fixtures consist of:

- \neg Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- ¬ Copper-free (<1%) precision die-cast aluminum housing and ring/faceplate.
- \neg Frosted, tempered, silk-screened, flat glass diffuser.
- ¬ Custom molded, anti-aging gasket(s).
- ¬ Custom MCPCB utilized to maximize heat dissipation and promote long LED life.
- ¬ Input voltage: 120-277 V (50 / 60 Hz), integral driver.
- ¬ Pre-wired factory sealed cable for external electrical connection included.
- The luminaire may be configured with numerous options and multiple standard finishes.
 Not all options are available in all configurations. Consult factory for more information about specification sheet details to build your light.
- ¬ Stainless steel recessed rough-in kit to be ordered separately.
- ¬ Product meets Buy American Act (BAA) requirements within ARRA.
- ¬ 5-year warranty.
- Marine Grade finish.
- ¬ Suitable for Natatorium applications.
















FINISHES

- AN-96 / Iron gray / Textured
- GR-94 / Aluminum metallic / Textured
- \bigcirc WH-87 / White / Textured
- BK-81 / Black / Textured
- RB-10 / Iron rust / Textured



Scan here for installation instructions



LUMEN OUTPUT								
	27K	30K	35K	40K	50K			
9W	572	592	613	633	671			

 ${\tt PERFORMANCE\,iN\,LIGHTING\,reserves\,the\,right\,to\,make\,all\,necessary\,changes\,without\,prior\,notice}$

Order Guide - INSERT+2 V

Order code example: I+2V-9W-30K-WH-120V



I+2V						
SERIES	Wattage	ССТ	Finish	Voltage	Controls	Accessories
I+2V Insert+2 V	9 9W* (max)	27K 2700K 30K* 3000K 35K 3500K 40K* 4000K 50K 5000K	AM Aluminum Metallic* IG Iron Gray* IR Iron Rust BK Textured Black WH Textured White* CC Custom Color	UNV 120-277V* 120V 120V only	O-10V 0-10V Dimming Driver* ELV 120V Line-Voltage Dimming Driver Contact Factory for Remote driver options	PLT Adaptor plate; specify dimensions BABAA Build America Act compliant Contact Factory about adaptor plate custom options

STANDARD OPTION, SHORTER LEAD TIME, NO MOQ


ROUGH IN INCLUDED WITH FIXTURE - CAN BE SHIPPED AHEAD 80 CRI STANDARD - OTHER OPTIONS AVAILABLE





REQUIRED FOR INSTALLATION Included with Fixture

DESCRIPTION	FINISH	PART NUMBER
INSERT+ 2 V		
Rough-In kit INSERT+ 2 V		3121497



3121497