

INSERT+ 1V BOLLARD



Pathway bollard series. Fixtures consist of:


- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free (<1%) precision die-cast aluminum housing and ring/faceplate.
- Copper-free (<1%) aluminum extruded post.
- Frosted, tempered, silk-screened, flat glass diffuser.
- Custom molded, anti-aging gasket(s).
- Custom MCPCB utilized to maximize heat dissipation and promote long LED life.
- To be used with a 24-V low-voltage driver (ordered separately, consult factory for more information).
- Optional, integral, line-voltage, passive infrared motion sensor (PIR SENSOR versions).

- Pre-wired factory sealed cable for external electrical connection included.
- Aluminum ground base plate included for bollards.
- The luminaire may be configured with numerous options and multiple standard finishes. Not all options are available in all configurations. Consult factory for more information about specification sheet details to build your light.
- Product meets Buy American Act (BAA) requirements within ARRA.
- 5-year warranty.



FINISHES

- AN-96 / Iron gray / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- BK-81 / Black / Textured
- RB-10 / Iron rust / Textured



Lumen Output	3K	4K
INSERT+ 1V BOLLARD	319	333



Scan here for
installation instructions

PERFORMANCE IN LIGHTING reserves the right to make all necessary changes without prior notice

PERFORMANCE IN LIGHTING USA, Inc.
2621 Keys Pointe Conyers GA 30013 - United States
Tel: 770 822 2115

info.usa@pil.lighting
www.performanceinlighting.com/us/us/

REVISION 06
10/24

Order Guide – INSERT+1V BOLLARD



Order code example: I+1VBOL-24"-5W-30K-WH-24V-RDRDIM

I+1VBOL						
SERIES	Bollard Height	Wattage	CCT	Finish	Voltage	Accessories
I+1V BOLLARD Insert+1V Bollard	24" Standard Height 47" Max Height XX" Specify Height Must Be Below Max	5 5W* (max)	30K 3000K* 40K 4000K* RGBW RGBW	AM Aluminum Metallic* IG Iron Gray* IR Iron Rust BK Textured Black WH Textured White* CC Custom Color	24V 24V Low-voltage only Contact Factory for Remote driver options	RDR Remote LED Driver (One Per Fixture) 17097 RDRDIM Remote 0-10V LED Driver (1-15 Fixtures) 17029 BABAA Build America Buy America Act compliant RP For use with certain railing products, no rough-in or post included or required

STANDARD OPTION, SHORTER LEAD TIME, NO MOQ
80 CRI STANDARD - OTHER OPTIONS AVAILABLE

RGBW ACCESSORIES

RGBW CONTROL ACCESSORIES ARE
TO BE INSTALLED IN REMOTE LOCATION

NON-INTEGRAL INSTALLATION

Power Supply



17433
Kit driver 48V



17096
Kit driver 48V WP


RF Controls



3104173
RGBW RF controller 4 channel
(0.35A each CH)



31041730
RGBW RF controller WP 4 channel
(0.35A each CH)



310429
RGBW hand held remote

DMX Controls



178973
RGBW DMX enabler/decoder 4
channel (0.35A each CH)



1789730
RGBW DMX enabler/decoder WP 4
channel (0.35A each CH)