BLIZ ROUND CROSS

Performance Lighting





Ceiling and wall mount series. Fixtures consist of:

- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free precision die-cast aluminum housing and ring/faceplate.
- High transmittance, internally coated, soda-lime pressed glass diffuser, thermally and chemically quenched to strengthen the impact resistance and reduce the effect of rapid temperature changes.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- Custom MCPCB utilized to maximize heat dissipation and promote a long LED life.
- 100% uniform diffused light emission.
- Input voltage: 120-277 V (50 / 60 Hz), integral 0-10 V dimming driver.
- Optional, integral, high-frequency motion-sensor operating at a frequency of 5.8 GHz +/- 75 MHz (HF versions).
- Optional, integral, emergency battery-pack designed for a minimum operation of 90 minutes (EMPK versions).
- Consult factory for dimming options, custom finishes, and non-cataloged CCT (Kelvin) options.
- 5-year warranty on components.
- 10-year warranty on glass.
- Marine Grade finish.
- Suitable for Natatorium applications.

IP 65 · WET · PRONTO · cULus LISTED · ADAi COMPLIANT · HF · 0-10 V · 90′ · IK 08 5 J

FINISHES

- **AN-96** / Iron gray / Textured
- **GR-94** / Aluminum metallic / Textured
- **WH-87** / White / Textured
- **BK-81** / Black / Textured
- **RB-10** / Iron rust / Textured

12"



BLIZ ROUND
30

16"



BLIZ ROUND
40

Lumen Output	2700K	3000K	3500K	4000K
BLIZ 30 - 10W (min)	689	716	743	770
BLIZ 30 - 20W	1377	1431	1485	1540
BLIZ 30 - 30W (max)	2096	2178	2260	2343
BLIZ 40 - 10W (min)	663	685	707	728
BLIZ 40 - 20W	1326	1370	1413	1456
BLIZ 40 - 30W	1989	2054	2120	2184
BLIZ 40 - 40W (max)	2652	2739	2826	2912

Scan here for installation Instructions

Performance in Lighting reserves the rights to make all necessary changes without prior notice.
Performance in Lighting - 2621 Keys Pointe - Conyers, Georgia 30013 - USA - voice 770.822.2115 - info.usa@pil.lighting
www.performanceinlighting.com

Rev. 08/26/2026

Order Guide - BLIZ ROUND CROSS

Order code example **BRD-CROS-30-10W-3K-AM-UNV-010V-VSIGN**

Series	Housing Style	Wattage	CCT	Finish	Voltage	Dimming	Options/ Accessories
BRD-CROS Bliz Round Cross	**30** Round 12" **40** Round 16"	**10W** 24 watt **20W** 20 watt **30W** 30 watt (Bliz 30 max) **40W** 40 watt (Bliz 40 max) **XX** Specify wattage Must be below max	80 CRI std. **27K** 2700K **3K** 3000K **35K** 3500K **4K** 4000K **5K** 5000K **RED** Static Red **BLU** Static Blue **GRN** Static Green	**AM** Aluminum Metallic **IG** Iron Gray **IR** Iron Rust **BK** Textured Black **WH** Textured White **CC** Custom Color	**UNV** 120-277V	**Blank** Non-dimming **010V** 0-10V Dimming Driver **ELV** 120V Line-Voltage Dimming Driver *For more options contact factory*	**VSIGN** Vertical Signage **HSIGN** Horizontal Signage **REM** Remote Emergency Battery Back-up **TP** Tamper proof hardware

CONSULT FACTORY FOR OTHER AVAILABLE OPTIONS NOT SHOWN ABOVE



CROSS TRIM



STANDARD TRIM



Fixture shown with CON2/CON4 option colored for contrast

Power Supply



17433
Kit driver 48V



17096
Kit driver 48V WP

RF Controls



3104173
RGBW RF controller 4 channel
(0.35A each CH)



31041730
RGBW RF controller WP 4 channel
(0.35A each CH)



310429
RGBW hand held remote

DMX Controls



178973
RGBW DMX enabler/decoder
4 channel (0.35A each CH)



1789730
RGBW DMX enabler/decoder WP
4 channel (0.35A each CH)



11015
Terminating Resistor



110150
Terminating Resistor WP

Performance in Lighting reserves the rights to make all necessary changes without prior notice.
Performance in Lighting - 2621 Keys Pointe - Conyers, Georgia 30013 - USA - voice 770.822.2115 - info.usa@pil.lighting
www.performanceinlighting.com