

BLIZ ROUND CROSS




- Ceiling and wall mount series. Fixtures consist of:
- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
 - Copper-free precision die-cast aluminum housing and ring/faceplate.
 - High transmittance, internally coated, soda-lime pressed glass diffuser, thermally and chemically quenched to strengthen the impact resistance and reduce the effect of rapid temperature changes.
 - Custom molded, anti-aging gasket(s).
 - Stainless steel external hardware.
 - Custom MCPCB utilized to maximize heat dissipation and promote a long LED life.
 - 100% uniform diffused light emission.
 - Input voltage: 120-277 V (50 / 60 Hz), integral 0-10 V dimming driver.
- Optional, integral, high-frequency motion-sensor operating at a frequency of 5.8 GHz +/- 75 MHz (HF versions).
 - Optional, integral, emergency battery-pack designed for a minimum operation of 90 minutes (EMPK versions).
 - Consult factory for dimming options, custom finishes, and non-cataloged CCT (Kelvin) options.
 - Product meets Buy American Act requirements within ARRA.
 - 5-year warranty on components.
 - 10-year warranty on glass.
 - Marine Grade finish.
 - Suitable for Natatorium applications.



FINISHES


- **AN-96** / Iron gray / Textured
- **GR-94** / Aluminum metallic / Textured
- **WH-87** / White / Textured
- **BK-81** / Black / Textured
- **RB-10** / Iron rust / Textured

12"



BLIZ ROUND
30

16"



BLIZ ROUND
40

Scan here
for installation
instructions



Lumen Output	2700K	3000K	3500K	4000K
BLIZ 30 – 10W (min)	689	716	743	770
BLIZ 30 – 20W	1377	1431	1485	1540
BLIZ 30 – 30W (max)	2096	2178	2260	2343
BLIZ 40 – 10W (min)	663	685	707	728
BLIZ 40 – 20W	1326	1370	1413	1456
BLIZ 40 – 30W	1989	2054	2120	2184
BLIZ 40 – 40W (max)	2652	2739	2826	2912



**CROSS
TRIM**



**STANDARD
TRIM**

Order Guide - Bliz Round Cross

Order code example

BRD-CROS-30-AM-3K-277-NA-H/L-STANDARD

BRD-CROS

Housing Style	Wattage	Finish	Color Temperature	Voltage	Controls	Accessories	Optional Trim
30 Round 12" 40 Round 16" 30 30 watt (Bliz 30 MAX) 40 40 watt (Bliz 40 MAX) XX Specify Wattage must be below max	10 10 watt 20 20 watt 30 30 watt (Bliz 30 MAX) 40 40 watt (Bliz 40 MAX) XX Specify Wattage must be below max	AM Aluminum Metallic IG Iron Gray IR Iron Rust BK Textured Black WH Textured White CC Custom Color	27K 2700k 3K 3000k 35K 3500k 4K 4000k AMB 590nm Amber (turtle- friendly) RGBW* RGBW *See below for details	UNV 120-277V	NA Non Dimming 0-10V 0-10V Dimming Driver ELV 120V Line-Voltage Dimming Driver 1% One Percent Dimming Driver For more Options Contact Factory	EMPK Integral Emergency Battery back up CWEMPK Remote Cold Weather Emergency Battery back up (-4°F - 122°F) HF High Frequency Occupancy Sensor w/ daylight PHC H/L High-Low Occupancy Sensor	(See pictures above) Contact Factory for MOQ Standard Trim Eyelid Trim (15W Max) Cross Trim Visa Trim (15W Max) CON2 (double-gang j-box, adaptor plate and 1/2" knockouts) CON4 (double-gang j-box, adaptor plate and 3/4" knockouts) TP Tamper Proof hardware BABAA Build America Buy America Act compliant



Fixture shown with
CON2/CON4 option
colored for contrast

80 CRI STANDARD - OTHER OPTIONS AVAILABLE

REMOTE RGBW ACCESSORIES

Power Supply



17433
Kit driver 48V



17096
Kit driver 48V WP

RF Controls



3104173
RGBW RF controller 4 channel
(0.35A each CH)



31041730
RGBW RF controller WP 4 channel
(0.35A each CH)



310429
RGBW hand held remote

DMX Controls



178973
RGBW DMX enabler/decoder 4
channel (0.35A each CH)



1789730
RGBW DMX enabler/decoder WP 4
channel (0.35A each CH)



11015
Terminating Resistor



110150
Terminating Resistor WP

Revision 07
04/25