



BLIZ



BLIZ GUARD



BLIZ VISA



BLIZ VISA V

Surface-mount doorway and hallway lights and post mount series. Fixtures consist of:


- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free die-cast aluminum housing, ring, and faceplates.
- Copper-free aluminum extruded post.
- High transmittance, internally coated, pressed glass diffuser, thermally, and chemically quenched to strengthen the impact resistance and reduce the effect of rapid temperature changes.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- Custom MCPCB utilized to maximize heat dissipation and promote long LED life.
- Tiltable LED board mounting bracket allows for quick and easy installation.
- 100% uniform diffused light emission.

- Input voltage: 120-277 V (50 / 60 Hz), integral 0-10 V dimming driver.
- Five optional finishes available. Add finish suffix to any part number for textured Black (BK-81), Iron gray (AN-96), Aluminum metallic (GR-94), White (WH-87), Iron rust (RB-10) when not standard.
- Consult factory for dimming options, marine-grade, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options including static colors.
- Consult factory for custom signage options.
- Suitable for Natatorium applications.
- 5-year warranty on component.
- 10-year warranty on glass.
- Marine Grade finish.




FINISHES

- **AN-96** / Iron gray / Textured
- **GR-94** / Aluminum metallic / Textured
- **BK-81** / Black / Textured
- **WH-87** / White / Textured
- **RB-10** / Iron rust / Textured




BLIZ




Lumet Output	2700K	3000K	3500K	4000K
BLIZ Open – 10W	486	498	509	520
BLIZ Open – 19.5W	972	995	1017	1040
BLIZ Guard – 10W	326	334	341	349
BLIZ Guard – 19.5W	652	667	682	699
BLIZ Visa – 10W	297	304	311	318
BLIZ Visa – 19.5W	593	607	621	635
BLIZ Visa V– 10W	320	327	335	342
BLIZ Visa V– 19.5W	639	654	669	684



Scan here for
installation
Instructions



**BLIZ
VISA/V**



Order Guide - Bliz Bollard

Order code example

BZB-O-P20-10W-3K-AM-UNV-010V-SIGN

Series	Bollard Size	Wattage	CCT	Finish	Voltage	Dimming	Options/ Accessories
BZB-O Bliz Bollard Open Trim BZB-G Bliz Bollard Grill Trim BZB-V Bliz Bollard Visa Trim BZB-VV Bliz Bollard Visa Vertical Trim	P20* 20"H, 9"W P40* 40"H, 6"W <i>* Standard bollard size. For more options contact factory</i>	10W 10 watt (min) 19.5W 19.5 watt (max) XX Specify wattage must be below max	80 CRI std. 27K 2700K 3K 3000K 35K 3500K 4K 4000K AMB Static amber 590nm turtle-friendly	AM Aluminum metallic IG Iron gray IR Iron rust BK Textured black WH Textured white CC Custom color	UNV 120-277V	010V 0-10V dimming driver ELV 120V Line- voltage dimming driver <i>For more options contact factory</i>	SIGN Logo/Signage TP Tamper proof hardware

CONSULT FACTORY FOR OTHER AVAILABLE OPTIONS NOT SHOWN ABOVE

NOTE: TEMPLATE AND ANCHOR BOLTS INCLUDED WITH FIXTURE