

NIKKO+21 BOLLARD



Surface-mount doorway and hallway lights and post mount series. Fixtures consist of:



- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free die-cast aluminum housing, ring, and faceplates.
- High transmittance, internally coated, soda-lime pressed glass diffuser, thermally and chemically quenched to strengthen the impact resistance and reduce the effect of rapid temperature changes.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- High-efficiency COB, combined with an optimized passive cooling system, provides a long LED life.

- 100% uniform diffused light emission.
- Input voltage: 120-277 V (50 / 60 Hz), integral driver.
- Consult factory for dimming options, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options including static colors.
- Wall bracket and post accessories available (ordered separately).
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty on components.
- 10-year warranty on glass.
- Marine Grade finish.
- Suitable for Natatorium applications.



FINISHES

- AN-96 / Iron gray / Textured
- RB-10 / Iron rust / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- BK-81 / Black / Textured



NIKKO
+21 LED

| Lumen Output | 27K | 3K | 35K | 4K | 5K |
|----------------|-----|-----|-----|-----|-----|
| Nikko+21 | 784 | 803 | 821 | 840 | 858 |
| Nikko+21 Grill | 429 | 439 | 449 | 459 | 469 |
| Nikko+21 Visa | 367 | 381 | 395 | 409 | 423 |

11W Max Wattage



Open



Grill



V Shade



Scan here
for installation
instructions

Order Guide - Nikko+21 Bollard




Order code example


N21-V-11-IG-3K-120-NA-WB

80 CRI STANDARD - OTHER OPTIONS AVAILABLE


N21B-

| Trim Style | Wattage | Finish | Kelvin | Voltage | Controls | Accessories |
|---|--|--|--|------------------------|--|--|
| OP Open G Grill V Shade | 11 11 watt (max) XX Specify Wattage Must be below max | AM Aluminum Metallic IG Iron Gray IR Iron Rust BK Textured Black WH Textured White CC Custom Color | 27K 2700k 3K 3000k 35K 3500k 4K 4000k 5K 5000k 65K 6500k RED Static Red BLU Static Blue GRN Static Green RGBW* RGBW *See below for details | UNV 120-277V | NA Non Dimming 0-10V 0-10V Dimming Driver ELV 120V Line- Voltage Dimming Driver | REM Remote Mounted Emergency Battery Back Up WB Wall Bracket P7 7.8" Post P22 22.95" Post P32 32.79" Post BABAA Build America Buy America Act compliant  <p>COMPLETE UNIT 1A+1B = 2 codes 2A+1B = 3 codes COMPONENTS A luminaire B post</p> |


WALL BRACKET AND POSTS ARE SUITABLE FOR ONE OR TWO FIXTURES EACH




WB
Wall Bracket



P7
7.8" Post



P22
22.95" Post



P32
32.79" Post

Performance in Lighting reserves the right to make all necessary changes without prior notice.

Performance in Lighting - 2621 Keys Pointe - Conyers, Georgia 30013 - USA - voice 770.822.2115 - info.usa@pil.lighting
www.performanceinlighting.com

Revision 02
04/25

REMOTE RGBW ACCESSORIES

Power Supply



17433
Kit driver 48V



17096
Kit driver 48V WP

RF Controls



3104173
RGBW RF controller 4 channel
(0.35A each CH)



31041730
RGBW RF controller WP 4 channel
(0.35A each CH)



310429
RGBW hand held remote

DMX Controls



178973
RGBW DMX enabler/decoder 4
channel (0.35A each CH)



1789730
RGBW DMX enabler/decoder WP 4
channel (0.35A each CH)



11015
Terminating Resistor



110150
Terminating Resistor WP