

Fixture shown with vertical signage



Fixure shown with horizonal signage



Wall mount series. Fixtures consist of:

- ¬ Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- ¬ Copper-free precision die-cast aluminum housing and ring/faceplate.
- ¬ High transmittance, internally coated, pressed glass diffuser, thermally, and chemically quenched to strengthen the impact resistance and reduce the effect of rapid temperature changes.
- ¬ Custom molded, anti-aging gasket(s).
- ¬ Stainless steel external hardware.
- ¬ Custom MCPCB utilized to maximize heat dissipation

- and promote long LED life.
- ¬ 100% uniform diffused light emission.
- ¬ Input voltage: 120-277 V (50 / 60 Hz), integral 0-10 V dimming driver.
- ¬ The luminaire may be configured with numerous options and multiple standard finishes. Not all options are available in all configurations. Consult factory for more information about specification sheet details.
- ¬ Product meets Buy American Act (BAA) requirements within ARRA.
- ¬ 5-year warranty.














## **FINISHES**

- AN-96 / Iron gray / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- BK-81 / Black / Textured
- RB-10 / Iron rust / Textured




**BLIZ OVAL** 



Scan here for installation instructions

## Order Guide - Bliz Oval





BO-

Wattage	Finish	Color Temperature	Voltage	Controls	Options
24W (max)  XX Specify wattage must be under max	AM Aluminum Metallic  IG Iron Gray  IR Iron Rust  BK Textured Black  WH Textured White  CC Custom Color	27K 2700K  3K 3000K  35K 3500K  4K 4000K  5K 5000K  65K 6500K  RED Static Red  BLUE Static Blue  GRN Static Green  AMB Static Amber (turtle-friendly)	UNV 120-277V	NA Non Dimming  0-10V 0-10V Dimming  ELV ELV Dimming	VSIGN Vertical Signage  HSIGN Horizontal Signage  REM Remote Emergency Battery Back-Up  TP Tamper Proof hardware