
## **INSERT+ 1V GLASS**





Recessed wall steplight series. Fixtures consist of:

- ¬ Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- ¬ Copper-free (<1%) precision die-cast aluminum housing and ring/faceplate.
- ¬ Frosted, tempered, silk-screened, flat glass diffuser.
- ¬ Custom molded, anti-aging gasket(s).
- ¬ Custom MCPCB utilized to maximize heat dissipation and promote long LED life.
- ¬ Screen-printed tempered glass front diffuser (GLASS options)
- ¬ To be used with a 24 V low-voltage driver (ordered separately, consult factory for more information).

- ¬ Pre-wired factory sealed cable for external electrical connection included.
- ¬ The luminaire may be configured with numerous options and multiple standard finishes. Not all options are available in all configurations. Consult factory for more information about specification sheet details to build your light.
- ¬ Stainless steel recessed rough-in kit to be ordered separately.
- ¬ Product meets Buy American Act (BAA) requirements within ARRA.
- ¬ 5-year warranty.












Standard finishes:

○ WH-87 / White / Textured

Lumen Output	3K	4K
INSERT+1 GLASS	160	167





Scan here for installation instructions



## Order Guide - INSERT+1V GLASS

Order code example:

I+1VG						
SERIES	Wattage	ССТ	Finish	Voltage	Controls	Accessories
I+1VG Insert+1 V Glass	5 5W* (max)	30K 3000K 40K 4000K	WH Textured White*	24V 24V Low-voltage only		

\*STANDARD OPTION, SHORTER LEAD TIME, NO MOQ\*

80 CRI STANDARD - OTHER OPTIONS AVAILABLE

ROUGH IN INCLUDED WITH FIXTURE - CAN BE SHIPPED AHEAD



## **REQUIRED FOR INSTALLATION**

## INCLUDED WITH FIXTURE

DESCRIPTION	FINISH PART NUMBER
INSERT+ 1V GLASS	

